

+ Flexability + Durability + Capability

The Right Printing Plate For All Corrugated Board Print Applications

MGC

MacDermid MGC is a sheet photopolymer specifically designed to address all direct print corrugated board requirements.

MGC sheet photopolymer ensures high quality direct printing for the most demanding corrugated print surfaces. The soft plate durometer, 32 Shore A, provides excellent solids coverage, while its low tack and high resilience offer long and clean press runs. MGC has the added capability to image fine detail without the need to back mask, providing superior print quality and cycle time savings for the plate maker.

MacDermid Graphics Solutions delivers an unrivalled customer experience through technical expertise and constant innovation. Creating solutions that flex.

Key Features & Benefits

- Quick washout
- Holds the finest detail without the need to back mask
- Image fidelity for high-end graphic and halftone reproduction at all gauges
- No cupping allows for uniform impression at all process speeds
- Chip resistant, tack free and extremely durable

Segments

- Corrugated

Creating
solutions
that flex.

For more information, please contact:

500 Chattahoochee Row NW Suite D, Atlanta, GA 30318
macdermidgraphics.com
404.696.4565



+ MGC Photopolymer Plate

Elevate Your Print to the Next Level



Technical Specifications

MGC is available in thicknesses of 0.112" (2.84 mm) - 0.250" (6.35 mm) and in sizes up to 52" x 80" (1,320 mm x 2,032 mm). Please contact your MacDermid representative for details.

Reproduction capabilities

Halftones: 2 - 90% at 100 lpi (40 lines/cm)
 Fine lines: 0.005 in. (0.13mm) width
 Isolated dots: 0.015 in. (0.38mm) diameter

Fine lines and isolated dots using 0.250 (6.35 mm) plate

Plate processing*

Use with SOLVIT® M100 or SOLVIT® LO is recommended.
 Most other safe-solvent solutions may be used.

*Processing times for any particular job are determined by equipment, copy requirements, and plate thickness.

Ink/Solvent Compatibility

MGC plates have ink compatibility similar to natural rubber. Plates are compatible with water and alcohol-based inks containing up to 25% acetate. MGC is not recommended for oil-based inks, hydrocarbon solvents, or inks with acetate ester content higher than 25%.

Applications

MGC is a sheet photopolymer for use in corrugated post print markets and other flexo markets that require a soft durometer plate.

Recommended Processing Conditions*

Gauge	Durometer	Desired Relief	Back Exposure ^{1,2}		Face Exposure ²		Washout ³	Dry Time	Post Exposure ³	Detack ⁴
			(mJ/cm ²)	(sec)	(J/cm ²)	(min)				
(mil/mm)	(Shore A)	(mil/mm)	(mJ/cm ²)	(sec)	(J/cm ²)	(min)	(sec)	(hrs)	(min)	(min)
112/2.84	38	55/1.40	750	45	4,000-6,000	250-375	400	1.5-2	8	10
125/3.18	36	60/1.52	900	55	4,000-6,000	250-376	400	1.5-2	8	10
155/3.94	34	70/1.78	900	55	4,000-6,000	250-377	450	2-2.5	8	10
250/6.35	32	125/3.18	2300	45	8,000-10,000	500-625	650	2-2.5	8	10

*Contact your MacDermid representative for assistance in establishing proper processing conditions

1. Lamp intensity 16mW
2. Solvit QD washout times
3. Lamp intensity 17 mW
4. Lamp intensity 10 mW

MacDermid Graphics Solutions delivers an unrivalled customer experience through technical expertise and constant innovation. Creating solutions that flex.